

## **SUPPORT PIN INSTALLATION FOR SQUARE & ROUND**

Step 1: Place <u>lock</u> washer on Support Pin first

Step 1: Place <u>flat</u> washer on Support Pin second.

Slide Support Pin with washer up through the bottom half into the top half.

Align anti-turn knob and TIGHTEN TO 40 FT/LBS

**NOTE:** The Support Pin is a specialized pin machined to spec. Only this pin can be used in the Sign Post Saver

Phone: 403.223.1088 Web: www.signpostsavers.com

SLOT FOR NUT

FLAT WASHER

SUPPORT PIN

ALIGN ANTI-TURN KNOB



# **SIGN POST SAVER INSTALLATION FOR SQUARE & ROUND**

# **SQUARE**


# Step 1: INSTALL GROUND ANCHOR 3" ABOVE

**GROUND LEVEL** 

# 3 INCHES HEAVY DUTY GROUND ANCHORS

### ROUND

Step 1: INSTALL GROUND ANCHOR 3" ABOVE GROUND LEVEL



Step 2: INSERT ASSEMBLED SPS UNIT INTO SLEEVE AND SLEEVE INTO BASE

ASSEMBLED SPS UNIT -



3 INCHES ALL BASES MUST BE 40 GAGE THICK

Step 3:

Step 2: INSERT SPS UNIT OVER TOP BASE


ASSEMBLED SPS UNIT\_\_\_FITS OVER TOP THE BASE



TIGHTEN BOTTOM 2 SET SCREWS

WITH SAFETY CABLE, THEN TIGHTEN THE TOP 2 SET SCREWS WITH SAFETY

40 GAGE THICK



TIGHTEN 2 BOTTOM BOLTS & -SAFETY CABLE WITH WASHER \_ TIGHTEN 2 TOP SET SCREWS WITH
SAFETY CABLE AND WASHER

CABLE.

─ TIGHTEN 2 BOTTOM SET SCREWS WITH
─ SAFETY CABLE AND WASHER